



Materiale: Fusiolen® PP-R
Standard: DIN 16962, DIN EN ISO 15874
Colore: verde



SDR	Art.-Nr.	Diametro d [mm]	Diametro d1 [mm]	Diametro d2 [mm]	l [mm]	L [mm]	z [mm]	D [mm]	Peso [kg]	Sistema	Confezione	GP	Prezzo €/pz.
<i>saldatura a tasca in entrambi i lati</i>													
	0011109	20	16	13,50	14,5	39,0	11,5	24,5	0,009	•	10	A	0,69
	0011110	25	16	16,50	16,0	38,0	9,0	26,0	0,012	•	10	A	0,82
	0011112	25	20	16,50	16,0	38,5	8,0	29,5	0,012	• •	10	A	0,74
	0011114	32	20	21,00	18,0	37,5	5,0	29,5	0,015	• •	5	A	1,12
	0011116	32	25	21,00	18,0	38,0	4,0	34,0	0,016	• •	5	A	1,12
	0011118	40	20	26,50	20,5	45,0	10,0	29,5	0,025	• •	5	A	2,10
	0011120	40	25	26,50	20,5	50,0	13,5	34,0	0,028	• •	5	A	2,10
	0011122	40	32	26,50	20,5	50,0	11,5	43,0	0,032	• •	5	A	2,10
	0011124	50	20	33,50	23,5	55,0	17,0	29,5	0,045	• •	5	A	3,17
	0011126	50	25	33,50	23,5	55,0	15,5	34,0	0,044	• •	5	A	3,17
	0011128	50	32	33,50	23,5	54,0	12,5	43,0	0,048	• •	5	A	3,17
	0011130	50	40	33,50	23,5	53,0	9,0	52,0	0,053	• •	5	A	3,17
	0011131	63	20	42,00	27,5	65,0	23,0	29,5	0,073	• •	1	A	6,04
	0011132	63	25	42,00	27,5	65,0	21,5	34,0	0,071	• •	1	A	6,04
6	0011134	63	32	42,00	27,5	62,0	16,5	43,0	0,080	• •	1	A	6,04
7,4	0011136	63	40	42,00	27,5	64,5	16,5	52,0	0,089	• •	1	A	6,04
9	0011138	63	50	42,00	27,5	63,5	12,5	68,0	0,107	• •	1	A	6,04
11	0011139	75	40	50,00	30,0	69,5	19,0	52,0	0,131	• •	1	A	6,89
17,6	0011140	75	50	50,00	30,0	63,0	9,5	68,0	0,141	• •	1	A	6,89
	0011142	75	63	50,00	30,0	71,0	13,5	84,0	0,170	• •	1	A	6,89
	0011143	75	20	50,00	30,0	65,5	21,0	34,5	0,113	• •	1	A	6,89
	0011144	75	25	50,00	30,0	65,5	19,5	34,5	0,111	• •	1	A	6,89
	0011145	75	32	50,00	30,0	69,5	21,5	52,0	0,140	• •	1	A	6,89
	0011151	90	50	60,00	33,0	75,0	18,5	68,0	0,193	• •	1	A	14,56
	0011152	90	63	60,00	33,0	78,0	17,5	84,0	0,224	• •	1	A	14,56
	0011153	90	75	60,00	33,0	81,5	18,5	100,0	0,273	• •	1	A	14,56
	0011155	110	63	73,50	37,0	86,0	21,5	84,0	0,356	• •	1	A	21,99
	0011157	110	75	73,50	37,0	89,0	22,0	100,0	0,383	• •	1	A	21,99
	0011159	110	90	73,50	37,0	99,0	29,0	120,0	0,500	• •	1	A	21,99
	0011161	125	75	84,00	40,0	101,0	31,0	100,0	0,518	• •	1	A	27,51
	0011163	125	90	84,00	40,0	99,0	26,0	120,0	0,588	• •	1	A	27,51
	0011165	125	110	84,00	40,0	112,0	35,0	147,0	0,832	• •	1	A	27,51