




			K [cm]	r [cm]	SU4 [pz.]	SU2 [pz.]	SU1 [pz.]	EUR/pz.
370.055.16.1	200	30	2,5	20			1	103,50
371.055.16.1	250	33,5	3	29	12		1	205,08
372.055.16.1	315	37	3	32,5	6		1	290,04

Curva 90° Geberit PE a gambo lungo e piccolo raggio



Campi di applicazione

- Per l'evacuazione delle acque reflue nere e bianche

Dati tecnici


Materiale	PE-HD
-----------	-------

Caratteristiche

- Resistente ai raggi UV

Art. no.	d, Ø [mm]	X1 [cm]	X2 [cm]	K1 [cm]	r [cm]	SU4 [pz.]	SU3 [pz.]	SU1 [pz.]	EUR/pz.
366.876.16.1	90	27	5	20	5	160	10		9,29
367.876.16.1	110	30	6	22	6	100	25	1	9,29

Curva 90° Geberit PE ridotta, senza gambo



Campi di applicazione

- Per l'evacuazione delle acque reflue nere e bianche

Dati tecnici

Materiale	PE-HD
-----------	-------

Caratteristiche

- Resistente ai raggi UV

Art. no.	d, Ø [mm]	d1, Ø [mm]	X [cm]	r [cm]	SU4 [pz.]	SU3 [pz.]	SU2 [pz.]	SU1 [pz.]	EUR/pz.
361.872.16.1	50	40	4	4			10	1	2,00
363.873.16.1	56	50	4	4			10	1	2,33
364.873.16.1	63	50	5	5			10	1	3,21
364.874.16.1	63	56	5	5	1600	100	10	1	3,49