




			K [cm]	SU4 [pz.]	SU3 [pz.]	SU2 [pz.]	SU1 [pz.]	EUR/pz.
360.045.16.1	40	4	2	2400	100	10		1,79
361.045.16.1	50	4,5	2	1600	100	10		2,00
364.045.16.1	63	5	2	1040	260	10		3,21
365.045.16.1	75	5	2	800	50	10		5,15
366.045.16.1	90	5,5	2	480	30	10		7,82
367.045.16.1	110	6	2,5	280	70	10		8,13
368.045.16.1	125	6,5	2,5	200	50	10	1	12,04
369.045.16.1	160	6,9	2	120	10		1	32,23
370.045.16.1	200	18	2,5	28	7		1	62,11
arc / Angolo: 88,5°								
361.088.16.1	50	6	2	1200	50	10		2,00
364.088.16.1	63	7	2	800	200	10	1	3,21
365.088.16.1	75	7,5	2	480	30	10	1	5,15
366.088.16.1	90	8	2	320	80	10		7,82
367.088.16.1	110	9,5	2,5	200	50	10		8,13
368.088.16.1	125	10	2,5	160	40	10	1	12,04
369.088.16.1	160	12	2,5	72	6		1	32,23

Curva Geberit PE a gambo lungo



Campi di applicazione

- Per l'evacuazione delle acque reflue nere e bianche

Dati tecnici

Materiale	PE-HD
-----------	-------

Caratteristiche

- Resistente ai raggi UV

Art. no.	d, ø [mm]	X1 [cm]	X2 [cm]	K1 [cm]	K2 [cm]	r [cm]	SU4 [pz.]	SU3 [pz.]	SU2 [pz.]	SU1 [pz.]	EUR/pz.
arc / Angolo: 45°											
367.046.16.1	110	14,7	6	11	2,5	—	160	40	10	1	12,80






				K1 [cm]	K2 [cm]	r [cm]	SU4 [pz.]	SU3 [pz.]	SU2 [pz.]	SU1 [pz.]	EUR/pz.
379.055.16.1	32	10	3	7	–	3	2400	100	10		2,21
360.055.16.1	40	15	3	12	–	3	1440	90	10		2,06
361.055.16.1	50	18	4	14	–	4	760	190	10		2,29
364.055.16.1	63	21	5	16	–	5	360	90	10		3,97
365.055.16.1	75	21	7	14	–	7	280	70	10		6,49
366.055.16.1	90	24	9	15	–	9	160	40	10		8,64
367.055.16.1	110	27	10	17	–	10	100	25			9,29
368.055.16.1	125	20	11	9	–	11	100	25		1	12,04
369.055.16.1	160	20	14	6	–	14	40	10		1	35,30



- La curva Geberit PE con angoli di 15°, 30°, 45° e 88,5° può essere saldata su entrambi i gambi con i manicotti termoelettrici Geberit
- La curva Geberit PE con angolo di 90° può essere saldata sul gambo lungo con i manicotti termoelettrici Geberit

Curva a segmenti Geberit PE



Campi di applicazione

- Per l'evacuazione delle acque reflue nere e bianche

Dati tecnici

Materiale	PE-HD
-----------	-------

Caratteristiche

- Resistente ai raggi UV

Art. no.	d, Ø [mm]	X [cm]	K [cm]	r [cm]	SU4 [pz.]	SU2 [pz.]	SU1 [pz.]	EUR/pz.
arc / Angolo: 30°								
370.030.16.1	200	15	2	20			1	62,11
371.030.16.1	250	16	3	42	24		1	86,29
372.030.16.1	315	17	3	47,3	12		1	103,98
arc / Angolo: 45°								
371.045.16.1	250	16,5	3	29	20	5	1	86,29
372.045.16.1	315	18	3	32,5	12		1	103,98