

MARKING:
FERRARI DN40
Pmax 2.5 bar
YY/WW
LOT NO


SW44
2 FLATS

**NOT: KOLİ İÇİ MİKTAR 10
TEK TEK POŞETLENECEKTİR.
POŞET ÜZERİNE ETİKET
YAPIŞTIRILACAKTIR.**

%40 CLOSED

3.1 certificate will be delivered

2	1 1/2" BSPT NIPPEL	0736 0016 02	2	AI31304/1.4301
1	KZ300 DN40 WB	0000 1004 92	1	AI31316L/1.4404
MONTAJ NO PART NR	PARÇA ADI / İTEmİNAmE	RESİM NO/ DRAWING NO	ADET QTY	MALZEME MATERIAL



DETAY A
ÖLÇEK 2 : 1

Certification Level	
Inspection Class	

1	Nipel ve markalama değiştirilmiştir. DBF0286			12.12.2016	SEDA ÇAKIR	BAHRİ BİÇİMSEVEN											
0	İlk yayın			17.06.2016	SEDA ÇAKIR	BAHRİ BİÇİMSEVEN											
Rev.	Description			Date	Drawer	Visa											
General Tolerances EN 22768 f	Angles related to shortest side (mm)				Chamfer & Radius (mm)				Linear Dimensions (mm)					A4	KUZUFLEX® Flexible Metal Hoses		
	From To	<10	10 50	50 120	120 400	>400	0,5 3	3 6	>6	<6	6 30	30 120	120 400			400 1000	>1000
Surface Roughness EN ISO 1302	Tol.	±1°	±30'	±20'	±10'	±5'	±0.2	±0.5	±1	±0.05	±0.1	±0.15	±0.2	±0.3	±0.5	Scale 1/1	Sheet 1/1
ADDITIONAL OPERATION	Heat Treatment	Net Weight	Material	Customer Article No	Item Name			Drawing No		Rev.							
		515 gr		031444	KZ300 DN40 WB ASSEMBLY L=210mm			0736 0016 00		1							

This drawing and all the information contained can not be used or reproduced, integrity or partially, without written authorization of KUZUFLEX Flexible Metal Hoses