


NOT: TRANSPARAN SARI PVC

NOT: ÜRÜN POŞETLEME MAKİNASINDA UZUNLAMASINA PAKETLENECEKTİR.

NOT: KOLİ İÇİ MİKTAR 175 ADET

141 (TIG)



DETAY A
ÖLÇEK 2 : 1

| MONTAJ NO PART NR | PARÇA ADI / ITEM NAME | RESİM NO/ DRAWING NO | ADET QTY | MALZEME MATERIAL |
|----------------------|---|-------------------------|----------|------------------------|
| 8 | LABEL | 0000 0611 36 | 1 | |
| 7 | TRANSPARENT NYLON | 0000 0600 08 | 1 | |
| 6 | 1/2" GASKET | 0000 0004 44 | 2 | NBR |
| 5 | RING 2 | 0000 0005 92 | 2 | AISI304/1.4301 |
| 4 | DN12 RING | 0000 0005 33 | 2 | AISI304/1.4301 |
| 3 | 1/2" BSP NUT (NICKEL PLATED) | 0000 0009 53 | 2 | CW617N/2.0402 |
| 2 | DN12 LINER | 0000 0004 03 | 2 | AISI303/1.4305 |
| 1 | KZ325 DN12 B + TRANSPARENT YELLOW PVC L=958mm (It is coated with PVC hose) | 0000 0041 89 | 1 | HOSE (AISI316L) PVC |

| Rev. | Description | Date | Drawer | Visa | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|--------------------------------------|------------|------------|---------------------|-----------------------------------|--------------------------------------|------|------|------------------------|--------------|-----------------------|-------|------|------------------------|------|-----------------------------------|----|--|-----------|--|-----------|--|--|------|-----|----|----|-----|------|-----|---|----|----|---|----|-----|-----|-----|-------|----|--|----------------------------------|------|-----|------|------|------|-----|------|------|----|-------|------|-------|------|------|------|-----------------------------------|--|----------------------|----------------|------------|----------|---------------------|-----------|--|--|--|--|------------|--|------|--|--|-----|--|-----|-----------------------------------|--|--|--|--|--------------|--|---|
| 1 | Etiket değiştirilmiştir. DBF0259 | 24.05.2016 | SEDA ÇAKIR | BAHRİ BİÇİMSEVEN | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0 | İlk yayın | 31.07.2015 | SEDA ÇAKIR | BAHRİ BİÇİMSEVEN | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="1"> <thead> <tr> <th>General Tolerances EN 22768 f</th> <th colspan="5">Angles related to shortest side (mm)</th> <th colspan="3">Chamfer & Radius (mm)</th> <th colspan="5">Linear Dimensions (mm)</th> <th colspan="2">Scale 1/1</th> <th colspan="2">Sheet 1/1</th> </tr> <tr> <td></td> <td>From</td> <td><10</td> <td>10</td> <td>50</td> <td>120</td> <td>>400</td> <td>0,5</td> <td>3</td> <td>>6</td> <td><6</td> <td>6</td> <td>30</td> <td>120</td> <td>120</td> <td>400</td> <td>>1000</td> <td colspan="2">A4</td> </tr> <tr> <td>Surface Roughness EN ISO 1302</td> <td>Tol.</td> <td>±1°</td> <td>±30'</td> <td>±20'</td> <td>±10'</td> <td>±5'</td> <td>±0.2</td> <td>±0.5</td> <td>±1</td> <td>±0.05</td> <td>±0.1</td> <td>±0.15</td> <td>±0.2</td> <td>±0.3</td> <td>±0.5</td> <td colspan="2">KUZUFLEX® Flexible Metal Hoses</td> </tr> </thead> <tbody> <tr> <td>ADDITIONAL OPERATION</td> <td>Heat Treatment</td> <td>Net Weight</td> <td>Material</td> <td>Customer Article No</td> <td colspan="5">Item Name</td> <td colspan="2">Drawing No</td> <td>Rev.</td> </tr> <tr> <td></td> <td></td> <td>---</td> <td></td> <td>---</td> <td colspan="5">KZ325 DN12 B ASSEMBLY L=1000mm</td> <td colspan="2">0736 0003 00</td> <td>1</td> </tr> </tbody> </table> | | | | | General Tolerances EN 22768 f | Angles related to shortest side (mm) | | | | | Chamfer & Radius (mm) | | | Linear Dimensions (mm) | | | | | Scale 1/1 | | Sheet 1/1 | | | From | <10 | 10 | 50 | 120 | >400 | 0,5 | 3 | >6 | <6 | 6 | 30 | 120 | 120 | 400 | >1000 | A4 | | Surface Roughness EN ISO 1302 | Tol. | ±1° | ±30' | ±20' | ±10' | ±5' | ±0.2 | ±0.5 | ±1 | ±0.05 | ±0.1 | ±0.15 | ±0.2 | ±0.3 | ±0.5 | KUZUFLEX® Flexible Metal Hoses | | ADDITIONAL OPERATION | Heat Treatment | Net Weight | Material | Customer Article No | Item Name | | | | | Drawing No | | Rev. | | | --- | | --- | KZ325 DN12 B ASSEMBLY L=1000mm | | | | | 0736 0003 00 | | 1 |
| General Tolerances EN 22768 f | Angles related to shortest side (mm) | | | | | Chamfer & Radius (mm) | | | Linear Dimensions (mm) | | | | | Scale 1/1 | | Sheet 1/1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | From | <10 | 10 | 50 | 120 | >400 | 0,5 | 3 | >6 | <6 | 6 | 30 | 120 | 120 | 400 | >1000 | A4 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Surface Roughness EN ISO 1302 | Tol. | ±1° | ±30' | ±20' | ±10' | ±5' | ±0.2 | ±0.5 | ±1 | ±0.05 | ±0.1 | ±0.15 | ±0.2 | ±0.3 | ±0.5 | KUZUFLEX® Flexible Metal Hoses | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| ADDITIONAL OPERATION | Heat Treatment | Net Weight | Material | Customer Article No | Item Name | | | | | Drawing No | | Rev. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | --- | | --- | KZ325 DN12 B ASSEMBLY L=1000mm | | | | | 0736 0003 00 | | 1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

| | |
|---------------------|--|
| Certification Level | |
| Inspection Class | |