


NOT: ÜRÜN ELDE 2YE KATLANARAK PAKETLENECEKTİR.

NOT: TRANSPARAN SARI PVC

MONTAJ NO PART NR	PARÇA ADI / ITEM NAME	RESİM NO/ DRAWING NO	ADET QTY	MALZEME MATERIAL
8	LABEL	0000 0611 36	1	
7	TRANSPARENT NYLON	0000 0600 14	1	
6	1/2" GASKET	0000 0004 44	2	NBR
5	RING 2	0000 0005 92	2	AISI304/1.4301
4	DN12 RING	0000 0005 33	2	AISI304/1.4301
3	1/2" BSP NUT (NICKEL PLATED)	0000 0009 53	2	CW617N/2.0402
2	DN12 LINER	0000 0004 03	2	AISI303/1.4305
1	KZ325 DN12 B + TRANSPARENT YELLOW PVC L=1458mm (It is coated with PVC hose)	0000 0041 89	1	HOSE (AISI316L) PVC



DETAY A
ÖLÇEK 2 : 1

Rev.	Description	Date	Drawer	Visa															
1	Etiket değiştirilmiştir. DBF0259	24.05.2016	SEDA ÇAKIR	BAHRİ BİÇİMSEVEN															
0	İlk yayın	06.08.2015	SEDA ÇAKIR	BAHRİ BİÇİMSEVEN															
General Tolerances EN 22768 f	Angles related to shortest side (mm)	Chamfer & Radius (mm)		Linear Dimensions (mm)					Scale 1/1		Sheet 1/1								
	From To	<10	10 50	50 120	120 400	>400	0,5 3	3 6	>6	<6	6 30	30 120	120 400	400 1000	>1000	A4		KUZUFLEX® Flexible Metal Hoses	
Surface Roughness EN ISO 1302	Tol.	±1°	±30'	±20'	±10'	±5'	±0.2	±0.5	±1	±0.05	±0.1	±0.15	±0.2	±0.3	±0.5				
ADDITIONAL OPERATION	Heat Treatment	Net Weight	Material	Customer Article No	Item Name					Drawing No		Rev.							
		---		---	KZ325 DN12 B ASSEMBLY L=1500mm					0736 0005 00		1							

Certification Level	
Inspection Class	