

Pompe per alto vuoto doppio stadio

- Rendimento elevato.
- Particolarmente leggera.
- Imballo singolo e flacone di olio minerale in dotazione.

- Il modelli WP3DE/V e WP8DE/V sono provvisti di vacuometro Ø80, elettrovalvola in aspirazione per evitare il riflusso dell'olio/aria atmosferica all'arresto della pompa, attacco 1/4" SAE M e 2 adattatori 1/4"SAE F x 3/8"SAE M e 1/4"SAE F x 5/16"SAE M.
- Il modello WP14DE è provvisto di elettrovalvola in aspirazione per evitare il riflusso dell'olio/aria atmosferica all'arresto della pompa, duplice attacco 1/4" SAE M e 3/8"SAE M con relativi tappi e 2 adattatori 1/4"SAE F x 3/8"SAE M e 1/4"SAE F x 5/16"SAE M.

SUGGERITA
R32


Imballo: 255 x 105 x 202 mm - 6,3 kg

Codice	Modello	Portata nominale	Vuoto finale	Alimentazione elettrica**	Potenza installata	Carica olio	Attacchi	Elettrovalvola (E) Vacuometro (V)
02099033	WP3DE/V	42 lt/min	2x10 ⁻² mbar	220-240/1/50-60	150 W	150 cc	1/4"-5/16"-3/8"	EV

**Altre tensioni e frequenze, su richiesta.

SUGGERITA
R32


Imballo: 338 x 138 x 244 mm - 12,4 kg

Codice	Modello	Portata nominale	Vuoto finale	Alimentazione elettrica**	Potenza installata	Carica olio	Attacchi	Elettrovalvola (E) Vacuometro (V)
02099034	WP8DE/V	128 lt/min	2x10 ⁻² mbar	220-240/1/50-60	368 W	325 cc	1/4"-5/16"-3/8"	EV

**Altre tensioni e frequenze, su richiesta.

SUGGERITA
R32


Imballo: 470 x 240 x 390 mm - 18 kg

Codice	Modello	Portata nominale	Vuoto finale	Alimentazione elettrica**	Potenza installata	Carica olio	Attacchi	Elettrovalvola (E) Vacuometro (V)
02099035	WP14DE*	230 lt/min	2x10 ⁻² mbar	230V 50/60Hz	750 W	560 cc	1/4"-5/16"-3/8"	E

* Pompa predisposta con duplice attacco 3/8" e 1/4"

**Altre tensioni e frequenze, su richiesta.

- Lightweight.
- Single packaging with one bottle of mineral oil.

- WP3DE/V e WP8DE/V models are equipped with Ø80 vacuum gauge, solenoid valve to prevent air/oil from flushing back when the pump is turned off, connection 1/4" SAE M and 2 adapters 1/4"SAE F x 3/8"SAE M and 1/4"SAE F x 5/16"SAE M.
- WP14DE model is equipped with solenoid valve to prevent air/oil from flushing back when the pump is turned off, double connections 3/8" SAE M and 1/4" SAE M with caps and 2 adapters for 1/4"SAE F x 3/8"SAE M and 1/4"SAE F x 5/16"SAE M.

 SUGGESTED
R32


Packaging: 255 x 105 x 202 mm - 6,3 kg

Code	Model	Swept volume	Ultimate vacuum	Power supply**	Nominal power	Oil charge	Connections	Solenoid valve (E) Vacuum gauge (V)
02099033	WP3DE/V	42 lt/min	2x10 ⁻² mbar	220-240/1/50-60	150 W	150 cc	1/4"-5/16"-3/8"	EV

**Other voltages and frequencies, on demand.

 SUGGESTED
R32


Packaging: 338 x 138 x 244 mm - 12,4 kg

Code	Model	Swept volume	Ultimate vacuum	Power supply**	Nominal power	Oil charge	Connections	Solenoid valve (E) Vacuum gauge (V)
02099034	WP8DE/V	128 lt/min	2x10 ⁻² mbar	220-240/1/50-60	368 W	325 cc	1/4"-5/16"-3/8"	EV

**Other voltages and frequencies, on demand.

 SUGGESTED
R32


Packaging: 470 x 240 x 390 mm - 18 kg

Code	Model	Swept volume	Ultimate vacuum	Power supply**	Nominal power	Oil charge	Connections	Solenoid valve (E) Vacuum gauge (V)
02099035	WP14DE*	230 lt/min	2x10 ⁻² mbar	230V 50/60Hz	750 W	560 cc	1/4"-5/16"-3/8"	E

* Pump with dual connections 3/8" and 1/4".

**Other voltages and frequencies, on demand.

Dichiarazione di Conformità



Noi, firmatari della presente, dichiariamo sotto la nostra esclusiva responsabilità, che le macchine, modello :

WP8D
e tutte le proprie varianti

destinate ad essere utilizzate per :


creare il vuoto in serbatoi, impianti a tenuta, ecc...aspirando miscele a base di aria e gas non corrosivi, non esplosivi e non pericolosi.

sono progettate secondo quanto prescritto dalle direttive :

- | | |
|--------------|--|
| • 2006/42/CE | Direttiva macchine |
| • 2014/30/UE | Direttiva sulla compatibilità elettromagnetica |
| • 2014/35/UE | Direttiva sulla bassa tensione. |

Castel San Niccolò
11/05/2016

Gastone Vangelisti
(Presidente)



Declaration of Conformity



We, signers of this declaration, declare under our own exclusive responsibility, that unit, model:

WP8D
and all its versions

manufactured in our company and to be used for:

make vacuum in tanks, seal systems etc...sucking air and non-corrosive, explosive and dangerous gas mixtures

Are designed according to the following directives prescriptions:

- **2006/42/CE** **Machines directive**
- **2014/30/UE** **Directive on electromagnetic compatibility**
- **2014/35/UE** **Directive on low voltage**

Castel San Niccolò
11/05/2016

Gastone Vangelisti
(Presidente)

